

Pre Sail Ob La Di!

1. Wash deck.
2. Get One Bag of Ice.
3. Pump bilge and vacuum remaining water out of bilge.
4. Deploy instruments:
 - a. Deploy Garmin Chartplotter: attach two wires, place on mount then remove cover and stow cover in cubby above nav station;
 - b. Deploy Race Master on Mast;
 - c. Stow four instruments covers in sink;
 - d. Turn on DC battery 1 and DC panel Main breaker;
 - e. Turn on "Instruments" right side DC panel 4th down, white switch;
 - f. Deploy two Tacktick remote instruments on range cover next to sink;
 - g. Turn on Tacktick by a remote.
5. Deploy Go Pros.
6. Deploy hand-held radio.
7. Set out Jib Sheets.
8. Run Spinnaker tapes (All Spin items are racing only).
9. Set out Spin Guys (tail above jib sheet) & Spin Sheets (tail under spin sheet).
10. Set up Spin Pole starboard side.
11. Set fore-stay length for racing:
48'11" for Light Air, 48'8" above 12kts and 48'7" above 25kts.
12. Remove main cover, stow below port side aft.
13. Bend mainsail on boom if necessary. Tack, then clew then halyard to head.
14. Uncoil Main Sheet and Fine Tune.
15. Unfurl pendants.
16. Deploy three winch handles from sink to pockets.
17. Check oil and transmission fluid.
18. Start engine, check that water exits aft.
19. Untie tiller, stow line on engine cover below deck.
20. Deploy tiller extension.
21. Verify dock & spring lines are ready to be removed from boat.
22. Turn off AC shore power at dock and remove yellow power cord from boat.
23. Make sure correct sails are on-board, remove extra sails.
24. Remove all extra items, especially important if this is a race.
25. Clear lines: out-haul, down-haul, halyards, pole topping lift, back-stay, traveler, check stays, Cunningham & Boom Vang.
26. Check shroud telltales.
27. Set up Main Reefing line if necessary.